



# XRN-3220RB2

32CH NVR with 12th gen. Intel® Processor



## Key Features

- 32CH, 32MP resolution
- SATA 8 HDD Bays (up to 80TB)
- Up to 520Mbps recording / transmission bandwidth
- Easy Channel/Event/Alarm configuration
- Virtual Channel View
- Dynamic layout
- Built-in Support for Web Management (up to 100)
- Compatible with Wisenet Viewer, Wisenet mobile
- NDAA compliant and TPM integrated
- Manual event support

# XRN-3220RB2

32CH NVR with 12th gen. Intel® Processor



## Specifications

Display		
Network camera	Inputs	Max. 32CH
	Resolution	32MP ~ CIF
	Protocols	SUNAPI, ONVIF
Decoding	Local Display	[Dual Display] HDMI 1: 3840 x 2160 (30Hz) HDMI 2: 1920x1080 (60Hz)
	Multi Screen Display	[Local Monitor] - Dynamic layout, Virtual channel view - Clone Mode : Up to 64 Division - Expand Mode : HDMI1 up to 32 Div. HDMI2 up to 16 Div. [Web] 1/ 2H/ 2V/ 3V/ 4/ 6/ 8/ 9
	Resolution	32M(15fps, H.265 Only), 12M(30fps, H.265 Only), 8.3M(4ch@30fps), 1080p(16ch@30fps), 720P(32ch@30fps), D1(48ch@30fps)
Intelligent Analysis		
AI Search	Object Attribute	Compatible with Hanwha AI Cameras
Performance		
Operating System	Embedded	Linux
Record	Compression	H.265, H.264, MJPEG
	Recording Bandwidth	Distributed mode : Up to 520 Mbps Normal mode : Up to 300 Mbps {RAID mode} Normal : Up to 520 Mbps Degradе/ Rebuild : Up to 520 Mbps
	Resolution	32MP ~ CIF
	Mode	Normal, Dual Stream, Schedule(Continuous/Event), Event (Pre/Post), Bookmark
	Event Trigger	Alarm Input, Video Loss, Camera Event(Sensor, MD, Video Analytics, Defocus, Audio), Dynamic Event, User Event
	Event Action	e-Mail, Event Push, PTZ Preset, Alarm Out, Buzzer, Monitor Out, FTP, SUNAPI Command, Shutdown
Search & Play	Playback Bandwidth	Up to 200Mbps(32CH simultaneously)
	User	Max. 4 Users (Local 1, Remote 3)
	Simultaneous playback	Max. 80CH(Local 32CH, Remote 16CH per user)
	Fisheye Dewarping	Support (Local 1CH), CMS
	Mode	Time/ Event/ Text/ ARB/ Bookmark/ Smart search
	Resolution	CIF ~ 32MP (Up to H.264 9MP, H.265 32MP)
	Playback Control	Fast/Slow Forward / Backward, Move one step Up / Down

Storage	Supported HDD	Up to 10TB
	HDD Slot	SATA 8ea(Max. 80TB, Non-RAID mode), Hot swap
	External	iSCSI storage
	RAID	RAID-5/6(Array Size : 8 HDDs x 1 Array)
Backup	File backup	Recorder/SEC/AVI/JPG(Local), AVI/PNG(Network)
	Function	Multi channel(Up to 16CH) Play, Date-Time/Title display

Network		
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, RTCP, NTP, HTTP, DHCP (Server, Client), SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)	
DDNS	Hanwha DDNS	
Transmission Bandwidth	Max. 520Mbps	
Audio	Input/Output	32 CH(network)
	Compression	G.711, G.726, AAC(16/48KHz)
	Audio Communication	2-Way
Max Remote Users	Search(3), Live Unicast(10), Multicast(20)	
Security	IP address filtering, User access Log, 802.1x, TLS, Encryption Device certificate(Hanwha Techwin Root CA), Signed firmware, TPM support	
Web viewer	Supported OS	Windows10 or higher, macOS 13.5.2 or higher
	Supported browser	Google Chrome, Microsoft Edge, Mac Safari
Viewer Software	SSM, Webviewer, Wisenet Viewer, Wisenet mobile Support CGI(SUNAPI) for integration to 3rd party VMS	

Functions		
Camera Setup	Register	Auto, Manual
	Item	IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup (4, 8 point polygon) Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSNR, Shutter, SDR, DIS), Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage
	Control	Via GUI, Webviewer, SPC-2000/2001
PTZ	Preset	300 Presets
	Support Model	iOS, Android
	Protocol Support	RTP, RTSP, HTTP, CGI(SUNAPI)
Smart phone	Control	Live 16CH(Multi-Profile Support), Playback 4CH
	Max. Remote Users	Search(3), Live Unicast(10)
Redundancy	Failover	N+1
	ARB	Support
Easy configuration	P2P(QR code)	

Interface		
Front	Indicator	HDD, Alarm, Power, Record, Backup, Network, RAID
Storage	Yes	
Reset	Power button	
HDD Key Lock	Yes	
HDMI	2EA ( Playback/Setup → HDMI1) HDMI1 : 3840x2160 30Hz HDMI2 : 1920x1080 60Hz	
Audio	Out 1EA (3.5mm Audio Jack)	
Ethernet	RJ-45 3EA (LAN/WAN, 1Gbps)	
Alarm	In 8EA, Out 4EA	

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com).

Hanwha Vision is formerly known as Hanwha Techwin.

USB	4EA(Front 2 x USB 2.0, Rear 2 x USB 3.0)
Power inlet	AC 1EA
<b>System</b>	
Log	Log List Max. 100,000 (System Log, Event Log each)
System Control	Mouse(include wireless), Keyboard(include wireless), Web, Controller (SPC-2000/2001)
Language	English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech, Portuguese, Danish, Romanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese
<b>Environmental</b>	
Operating Temperature	0°C to +40°C(32°F to 104°F)
Operating Humidity	20% ~ 85% RH
<b>Electrical</b>	
Power Input	100 ~ 240 VAC $\pm$ 10%; 50/60 Hz, 1.7A
Power Consumption	Max. 162W (553BTU with HDD 8ea)
<b>Mechanical</b>	
Color / Material	Black / Metal
Dimension (WxHxD)	438 x 86 x 434.9 mm
Weight	8.8Kg (19.4lb, Except HDD)

XRN-3220RB2



32CH NVR with 12th gen. Intel® Processor



CAD

Unit:mm [inch]

XRN-6420RB2\_XRN-3220RB2 RECORDER



Revision	V1.1
Revision Date	25/01/17
Paper Size	A1
Unit	mm [inch]
Scale	1:2

© Hanwha Vision Co., Ltd. All right reserved.